



VCR REAL TIME

MODEL CVR1030 - 30 Hour



CAPABILITIES & FEATURES

- II DIFFERENT RECORDING/PLAYBACK MODES AVAILABLE
- AUTO RECORDING AND PLAYBACK IN L6H, L18H, L30H REAL TIME MODES ARE AVAILABLE.
- EASY MODE SETTING AND CHECKING ON SCREEN DISPLAY
- BUILT-IN DATE / TIME GENERATOR
- BUILT-IN RECHARGEABLE BACK-UP BATTERY (1 WEEK)
- AUTO REPEAT RECORDING & ONE SHOT RECORDING
- ALARM RECORDING (RECORD DURATION IS ADJUSTABLE)
- TIMER RECORDING (9 PROGRAM/1 WEEK)
- SERIES RECORDING
- RECORD LOCK FUNCTION FOR AVOIDING UNINTENDED OPERATION.
- FOUR-HEAD DOUBLE AZIMUTH SYSTEM (EP 4 HEAD SYSTEM)
- DIAMOND-LIKE CARBON COATING ON UPPER CYLINDER
- FREE VOLTAGE POWER SOURCE
- PC CONTROL FUNCTION (OPTIONAL)
- VIDEO LOSS DISPLAY
- THRU VIDEO OUT FOR MONITOR LOOP WITHOUT POWER SOURCE
- SECURITY LOCK FUNCTION FOR PREVENTING THEFT OF THE VIDEO CASSETTE

SPECIFICATIONS

GENERAL

RECORDING METHOD	Four head double Azimuth system
AUDIO RECORDING	In L6H, L18H, L30H modes
TAPE SPEED	11.12 mm/sec (L6H mode)
VIDEO CASSETTE	VHS ½" Video Cassette T-120 tape
REWINDING TIME	Approx. 3 mins. when using T-120 tape

VIDEO

INPUT	BNC: 1V _{p-p} , 75Ω (unbalanced)
OUTPUT	BNC: 1V _{p-p} , 75Ω (unbalanced)
HORIZONTAL RESOLUTION	MONOCHROME MODE: 350 TV lines

AUDIO

LUMINANCE SIGNAL	-8dBm, Phono Jack, 47KΩ, (unbalanced)
COLOR SIGNAL	-7dBm, Phono Jack, 600Ω, (unbalanced)
SIGNAL-TO-NOISE RATIO	43dB (2-hour mode)

OTHER

OPERATING TEMPERATURE RANGE	41°F to 104°F (5°C to 40°C)
OPERATING HUMIDITY	80% or less
POWER SUPPLY	100 VAC - 240 VAC, 50/60 Hz
POWER CONSUMPTION	Approximately 14W
EXTERNAL DIMENSIONS (WxHxD)	14.17" x 3.54" x 12.28" 36 cm x 9 cm x 31.2 cm
WEIGHT	9.25 lbs. (4.2 kg)

Specifications subject to change without notice

